

TRAFFIC SIGN DETECTION AND POSITIONING FROM GOOGLE STREET VIEW STREAMLINES

Victor J. D. Tsai

Professor and Chair

Department of Civil Engineering

National Chung Hsing University

250 Kuokuang Road, Taichung City 40227, TAIWAN

jdotsai@nchu.edu.tw

ABSTRACT

Since Google Street View (GSV) services provide volumetric street view panoramas with associated geo-referenced information, this research aims to explore useful information from GSV streamlines. This research aims on developing an internet platform that integrates Google Maps API, HTML5 and JavaScript routines for accessing the GSV panoramas and associated orientation parameters in order to identify traffic signs and to determine their georeferenced positions. Being under development using OpenCV, OpenMP and C++, various techniques in detecting, extracting, recognizing, and positioning of traffic signs from cropped GSV streamlines along user-selected routes are primarily concerned for low-cost, volumetric and quick establishment of infrastructural database in public transportation networks towards value-added Location-Based Services.

KEYWORDS: Google Street View (GSV), Google Maps API, traffic sign detection and recognition.

INTRODUCTION

Traffic sign detection and recognition (TSDR) has drawn considerable research attention on developing intelligent transportation systems (ITS) and autonomous vehicle driving systems (AVDS) since the 1980's. A TSDR system is normally composed in two specific phases: detection and recognition for identifying traffic signs from road images taken from the installed in-vehicle camera (Nguwi & Kouzani, 2006; Lorsakul & Suthakorn, 2007; Huang *et al.*, 2008; Sallah *et al.*, 2011; Escalera *et al.*, 2011; Chen *et al.*, 2013). In the traffic sign detection (TSD) phase, the system searches for a region of interest (ROI) that may contain traffic signs within a road image by applying color segmentation or shape classification techniques. In the traffic sign recognition (TSR) phase, the system identifies the category and content of the signs by applying neural network learning, template matching, image classification, or genetic algorithms. Many literatures gave a brief review and comparison on color-based, shape-based, and other approaches for TSDR upon the three properties of traffic signs in color, shape, and inner content (Zakir *et al.*, 2011; Johansson, 2002; Nguwi & Kouzani, 2006; Fu & Huang, 2010; Escalera *et al.*, 2011; Feng, 2014). In practice, both TSD and TSR phases involve intensive work on image processing and analysis of a single image/video frame captured by the in-vehicle cameras. There remain a number of important issues in handling these images in real-time environment: lighting conditions, blurring effects, non-ideal orientations, paint deterioration, shape distortions, scale variations, occlusion, and confusion with other similar man-made objects (Nguwi & Kouzani, 2006). These unavoidable issues make the development of TSDR systems an interesting and challenging topic in the computer vision community.

On the other hand, since Google launched its street view services in 2007 and opened to internet communities and user contributions (Vincent, 2007; Anguelov *et al.*, 2010), many researches have been reported on various applications over street view images. Among these applications, Peng *et al.* (2010) developed a tour guiding video

from Google street view (GSV) images on intelligent mobile phones for interactive route recognition to car drivers. Similarly, Wu (2013) developed a panoramic image navigation system that integrates Google Maps routing and GSV panoramas for virtual touring on the Internet based on JavaScript and Ruby on Rails. Tsai & Chang (2012, 2013) developed an internet platform for accessing the orientation parameters of GSV panoramas in order to determine the global position of interested features by intersection from two overlapping GSV panoramas, which is suitable for volumetric data collection in establishing Location-Based Services (LBS) applications, in which the positional accuracy is not primarily concerned.

Unlikely to the general TSDR systems that deal with real-time images captured by the in-vehicle cameras, this research aims on developing techniques for detecting, extracting, and positioning of traffic signs from GSV streamlines along user-selected routes for low-cost, volumetric and quick establishment of infrastructural database in transportation networks. The framework and processes of the system under development is described in the remaining of this article.

TRAFFIC SIGN DETECTION USING GSV STREAMLINES

GSV Streamline Cropping

Natural color images were taken from a ring of eight cameras plus a fish-eye lens on top for producing the most popular 360° GSV panoramas (Anguelov *et al.*, 2010). Each available GSV panorama can be requested in an HTTP URL form using Google Maps JavaScript API, along with the projection type, the geodetic position of the street view car and its moving direction with respect to the North at the time of image capture. However, the GSV panorama may include severe distortions and ghost image in the upper portions (image from the 9th camera shooting the sky) and lower portions (rendered from other panoramas) as shown in Figure 1(a). Meanwhile, the tiled panorama accessed from GSV server is not truly 360° surrounded, but with overlapped portion in both ends in the horizontal direction. Therefore, the overlapped portion and the empty block in the last row of image tiles will be cropped as shown in Figure 1(b). Then, it would be good to locate ROIs on the central portions of $\pm 30^\circ$ in pitch (vertical angle), as shown in Figure 1(c), according to the vertical field of view of the camera lens (Tsai & Chang, 2012, 2013).

The Google Directions API makes it easy to plan a route on the Google Maps from selected start location to end location, returning in a JSON *routes* array with intermediate *legs* and *steps* or in an XML <DirectionsResponse> element. These *steps* and *legs* can be used to access available GSV streamlines along the route from which intermediate locations were interpolated from the connecting *steps* within a *legs* segment. The GSV panorama and its associated geodetic position and heading information were requested from the GSV server. The panoramas were then cropped for finding ROIs in the following steps that incorporate routines being developed using OpenCV, OpenMP, and C++.

Color Segmentation

Color tone is the most important and significant descriptor that simplifies and dominates feature identification and extraction in visual interpretation applications using color images. Basically, objects reflect the chromatic electro-magnetic *radiance* (EMR) and show various colors subjective to their reflectance to the three primary wavelengths in red (R), green (G), and blue (B) as designated by the CIE (Commission Internationale de l'Eclairage). Thus, all colors are seen as variable combination of the three primaries in the RGB color space, which is usually used in representing and displaying images. Color segmentation is the most common method applied for the initial detection of red, green, and blue traffic signs with white and black inner contents (Sallah *et al.*, 2011; Benallal & Menuier, 2003). Transformations from RGB color space into many other color spaces like HSI, HSL, HSV/HSB, IHLS, YUV, YC_bC_r, CIELAB, CIECAM, and CIELUV have been adopted in the literatures in color-based TSD. The thresholding segmentation approach was then applied to classify pixels as traffic sign or background (non-traffic-sign) for generating a binary image.



(a) Original tiled GSV panorama with horizontal overlapping, distortion, ghost, and empty block (size: 2048x1024)



(b) Cropped GSV panorama with truly 360° in horizontal and 180° in vertical (size: 1664x832)



(c) Cropped image with central 60° in vertical (size: 1664x277)

Figure 1. Cropping of the tiled GSV panorama (Zoom level = 3).

The HSI color model (Gonzalez & Woods, 1992) is adopted in this research for manipulating images with the transformation from the RGB space in the following relations:

$$I = \frac{1}{3}(R + G + B) \quad (1),$$

$$S = 1 - \frac{\min(R, G, B)}{I} \quad (2),$$

$$H = \begin{cases} \theta & \text{if } B \leq G \\ 360^\circ - \theta & \text{otherwise} \end{cases} \quad (3),$$

$$\text{where } \theta = \cos^{-1} \left(\frac{0.5[(R-G) + (R-B)]}{\sqrt{(R-G)^2 + (R-B)(G-B)}} \right) \quad (4).$$

Transformed I, S, H components are then segmented with certain threshold values for traffic sign in different colors, resulting in a binary image in which traffic signs object pixels are represented by 1's, and the background pixels by 0's. The resulted binary image was then analyzed and labeled for connected regions by connecting 8-connected pixels together. The bounding box of each connected components is set to extract the candidate ROI for filling holes within its internal boundary.

Shape Classification

Shape is also an important attribute of the traffic signs. Depending on the regulations, traffic signs are usually categorized as prohibitory or restrictive, mandatory, regulatory, and warning signs with regular shapes of circle, triangle, diamond, square or rectangle, and hexagon. Shape classification of each candidate ROI is carried out by evaluating the ROI's *Extent*, which is a ratio of the pixels in the ROI to the pixels of its bounding box (MathWorks, 2013), for candidate traffic signs in different shape patterns by setting appropriate thresholds (Sallah, 2011).

ROI Extraction and Normalization

Once a region was classified as traffic sign candidate, the image block within the bounding box of the ROI will be extracted from the cropped GSV panorama. Meanwhile, the background image will be filtered using the area within the internal boundary as a mask. Then the ROI image was normalized into a fixed dimension of 30 x 30 pixels by applying a homographic transformation in the form of homogeneous coordinates as following

$$\begin{bmatrix} u^* \\ v^* \\ w^* \end{bmatrix} = \begin{bmatrix} h_{11} & h_{12} & h_{13} \\ h_{21} & h_{22} & h_{23} \\ h_{31} & h_{32} & 1 \end{bmatrix} \begin{bmatrix} u \\ v \\ 1 \end{bmatrix} \quad (5),$$

where

$u' = \frac{u^*}{w^*}$ and $v' = \frac{v^*}{w^*}$ are transformed coordinates of the pixel at (u, v) of the original ROI image,

$h_{11}, h_{12}, h_{13}, h_{21}, h_{22}, h_{23}, h_{31}, h_{32}$ are coefficients of the transformation matrix.

Sign Content Recognition

The standard image templates of traffic signs in the Road Traffic Safety Portal Site (<http://168.motc.gov.tw>) of Taiwan were used as the database for recognizing the inner content of normalized image of extracted ROIs. Three approaches are evaluated to identify the traffic sign, including normalized cross-correlation (NCC) matching, multilayered feedforward back-propagation neural network (BPNN) with log-sigmoid activation function, and Hopfield neural network (HNN) with NCC matching. The database was divided into three groups: train, validation, and test set. NCC template matching is considered due to its simplicity on similarity measure, robustness to varying lighting conditions, and the ease of finding a statistical interpretation, although it may suffer from the presence of non-informative ROI pixels (Escalera *et al.*, 2011).

Sign Positioning

Once the normalized ROI has been recognized as a traffic sign, the original ROI templates from a pair of nearby GSV panoramas will be used to compute their corresponding centroids and to detect conjugate targets. Meanwhile, the centroid of the conjugate ROI templates are also used to compute the three-dimensional position of the target traffic sign by applying intersection from the known positions of the two GSV panoramas (Tsai & Chang, 2012, 2013). The positional and non-spatial information about the identified traffic signs will be stored in XML or KML formats for import into a transportation infrastructural database for value-added Location-Based Services.

SUMMARIES

This article describes the framework and processes of an on-going research that employs traffic sign detection and recognition (TSDR) and positioning from Google Street View (GSV) streamlines. The proposed system is divided into two major components: (1) an internet platform that employs Google Maps API and Web Service, CSS and HTML5 in developing an internet platform for accessing the orientation parameters of GSV panoramas along user selected routes; (2) TSDR core routines using OpenCV, OpenMP, and C++ that deal with identifying traffic signs and determining their positions by intersection from two overlapping cropped GSV panoramas. The proposed system is under development for efficient identification of traffic signs from the cropped GSV panoramas.

REFERENCES

- Anguelov, D., C. Dulong, D. Filip, C. Frueh, S. Lafon, R. Lyon, A. Ogale, L. Vincent, and J. Weave, 2010. Google Street View: Capturing the World at Street Level, *Computer*, vol. 43, no. 6, pp. 32-38.
- Benallal, M. and J. Meunier, 2003. Real-time color segmentation of road signs, *Canadian Conference on Electrical and Computer Engineering*, Montreal, Canada, May 4-7, 2003, vol. 3, pp. 1823-1826.
- Chen, Y., Y. Xie, and Y. Wang, 2013. Detection and recognition of traffic signs based on HSV vision model and shape features, *Journal of Computers*, vol. 8, no. 5, pp. 1366-1370.
- Escalera, S., X. Baro, O. Pujol, J. Vitria, and P. Radeva, 2011. Background on traffic Sign Detection and Recognition, *Traffic-Sign Recognition Systems*, Escalera et al., Springer, pp. 5-13, DOI: 10.1007/978-1-4471-2245-6_2.
- Feng, J., 2014. *Traffic Sign Detection and Recognition System for Intelligent Vehicles*, Master thesis, School of Electrical Engineering and Computer Science, University of Ottawa, Ottawa, Canada, 107 p.
- Fu, H. and Y.-S. Huang, 2010. A survey of traffic sign recognition, *International Conference on Wavelet Analysis and Pattern Recognition*, Qingdao, China, Hul. 11-14, 2010, pp. 119-124.
- Gonzalez, R. C. and R. E. Woods, 1992. *Digital Image Processing*, 2nd ed., Addison-Wesley.
- Huang, H., C. Chen, Y. Jia, and S. Tang, 2008. Automatic detection and recognition of circular road sign, *IEEE/ASME International Conference on Mechatronic and Embedded Systems and Applications (MESA 2008)*, Beijing, China, Oct. 12-15, 2008, pp. 626-630, DOI: 10.1109/MESA.2008.4735704.
- Johansson, B., 2002. *Road Sign Recognition from a Moving Vehicle*, Master's thesis, Center for Image Analysis, Uppsala University, Uppsala, Sweden, 72 p.
- Lorsakul, A. and J. Suthakorn, 2007. Traffic sign recognition for intelligent vehicle/driver assistance system using neural network on OpenCV, *The 4th International Conference on Ubiquitous Robots and Ambient Intelligence (URAI 2007)*, Pohang, Korea, No. 14-16, 2007, 6 p.
- MathWorks, Inc., 2013. Region and Image Properties, *MATLAB Image Processing Toolbox Help Documentation*.
- Nguwi, Y. Y. and A. Z. Kouzani, 2006. A study on automatic recognition of road signs, *IEEE Conference on Cybernetics and intelligent Systems*, Bangkok, June 7-9, 2006, pp. 1-6, DOI: 10.1109/ICCIS.2006.252289.

- Peng, C., B.-Y. Chen, and C.-H. Tsai, 2010. Integrated Google Maps and smooth Street View videos for route planning, *2010 International Computer Symposium (ICS 2010)*, Tainan, Taiwan, Dec. 16-18, 2010, pp. 319-324.
- Sallah, S. S. M., F. A. Hussin, and M. Z. Yusoff, 2011. Road sign detection and recognition system for real-time embedded applications, *International Conference on Electrical, Control and Computer Engineering*, Pahang, Malaysia, Jun 21-22, 2011, pp. 213-218.
- Tsai, V. J. D. and C. T. Chang, 2012. Feature Positioning on Google Street View panoramas, *XXII ISPRS Congress*, Melbourne, Australia, *ISPRS Annals of the Photogrammetry, Remote Sensing and Spatial Information Sciences*, vol. I-4, pp. 305-309.
- Tsai, V. J. D. and C. T. Chang, 2013. Three-dimensional positioning from Google street view panoramas. *IET Image Processing*, 7(3):229-239, DOI:10.1049/iet-ipr.2012.0323.
- Vincent, L., 2007. Taking online maps down to street level, *Computer*, vol. 40, no. 12, pp. 118-120.
- Wu, H.-P., 2013. *Integrating Google Street Views into Panoramic Navigation System*, Master thesis, Department of Civil Engineering, national Chung Hsing University, Taichung, Taiwan, 65 p.
- Zakir, U., I. Zafar, and E. A. Edirisinghe, 2011. Road Sign Detection and Recognition by Using Local Energy based Shape Histogram (LESH), *International Journal of Image Processing (JIIP)*, vol. 4, no. 6, pp. 567-583.